

LOW POWER MAINS TRANSFORMER

	Type of transformer	TS 20VA/16/18	
	Type of core	ΕI	
Primary rated voltage		230	V/50-60Hz
Number of pins primary voltage		1-5	
Secondary rated voltage		16V	18V
Rated secondary current		1,25A	1,2A
Number of pins seconda	ry voltage	8 – 10	6 - 10

We produce currently the 20 VA transformers with secondary voltage TS 20/16/18 TS 20/14 TS 20/14/18 TS 20/12/14 TS 20/14/16 We have the possibility of choosing the secondary voltage to customer needs

	Type of transforn Type of core	ner TS 3 E I	0/16/18	
Primary rated voltage		230)V/50-60Hz	
Number of pins primary vol	tage	1 – 5		
Secondary rated voltage		16V	18V	
Rated secondary current		1,25A	1,2A	
Number of pins secondary v	oltage	8-10	6 - 10	
We produce currently the 20 VA transformers with secondary voltage TS 30/16/18 TS 30/14/17				

We have the possibility of choosing the secondary voltage to customer needs

ATTEL	Type of transforme	er TS 40/16/18
	Type of core	ΕI
	Primary rated voltage	230V/50-60Hz
Number of pins primary voltage	1-5	
Secondary rated voltage	16V	18V
Rated secondary current	2,4A	2,2A
Number of pins secondary voltage	e 8 – 10	6 - 10

We produce currently the 40 VA transformers with secondary voltage TS 40/16/18 TS 40/17 TS 40/12/24 TS 40/14/17 TS 40/16/24 TS 40/17/24 We have the possibility of choosing the secondary voltage to customer needs



	Type of transformer	TS 50/20
	Type of core	ΕI
Danie	Primary rated voltage	230V/50-60Hz
Number of pins primary voltage	2 – 5	
Secondary rated voltage	20V	
Rated secondary current	2,4A	
Number of pins secondary voltage	7 – 12	
Foot – mounted transformer	65 x 70	

We produce currently the 40 VA transformers with secondary voltage TS 50/20 TS 50/14 TS 50/12/24 TS 50/16/24 TS 50/16/18 We have the possibility of choosing the secondary voltage to customer needs

	Type of transfor Type of core	mer TS 80/12/24 E I
Primary rated voltage	230	0V/50-60Hz
Number of pins primary voltage	2-5	
Secondary rated voltage	12V	24V
Rated secondary current	4,5A	4,5A
Number of pins secondary voltage	10-12 7-	12
Foot – mounted transformer	78	x 70

We produce currently the 80 VA transformers with secondary voltage TS 80/16 TS 80/16/18 TS 80/12 TS 80/12/24 We have the possibility of choosing the secondary voltage to customer needs

TRANSFORMER prices and delivery times depend on the amount of the contract. For further information on this issue provides sales division:

tel: 12 256 79 90 fax: 12 256 79 91

WELCOME TO COOPERATION.